



**Procesadores multimedia que simplifican las instalaciones en experiencias inmersivas con multiproyección**

## **ET-FMP50**

Procesadores multimedia que simplifican las instalaciones en experiencias inmersivas con multiproyección

### **Key Features**

Flujo de trabajo optimizado para simplificar los procesos

Ajuste de precisión para una calidad excepcional

Reproducción 4K fluida y continua



## ET-FMP50

<https://latam.connect.panasonic.com/br/es/products/projectors/et-fmp50>

<b>Type</b>	Box-type
<b>LAN</b>	RJ-45 x 1 for network connection, 10Base-T/100Base-TX, 1000Base-T, NDI® compatible, Art-Net compatible
<b>Audio Out</b>	3.5 mm stereo mini-jack
<b>USB</b>	USB 3.0 (Type A) x 2
<b>Video Format</b>	HAP <sup>1</sup> / H.264, 8-bit, 3840 x 2160 pixels, 60p, YPBPR 4:2:0, 300 Mbps / H.265, 8-bit, 4096 x 4096 pixels, 60p, YPBPR 4:2:0, 300 Mbps
<b>Audio Format</b>	AAC-LC, 16-bit, stereo
<b>Almacenamiento</b>	4 TB
<b>Sistema operativo</b>	Linux
<b>Power Supply</b>	(TBD)
<b>Dimensiones (AnxAxP)</b>	Approx. 210 mm x 44 mm x 295 mm (8 1/4" x 1 23/32" x 11 5/8" ) (Including feet) (TBD)
<b>Peso</b>	Approx. 2.0 kg (4.41 lbs) (Excluding AC adapter and cord) (TBD)
<b>Operating Environment</b>	Operating temperature: 0-40 °C (32-104 °F), operating humidity: 10-80 % (no condensation)
<b>Note</b>	1 ET-FMP50 only. Available from CY2024 Q4. 2 When four HDMI™ outputs are used simultaneously.